

Engineering Design Specification D05 Geometric Road Layout

Print version is uncontrolled. Current version is maintained on Wingecarribee Shire Council Website in searchable PDF format.

This document is a modified version of AUS-SPEC 0041
Geometric Road Layout

Working with you

WSC.NSW.GOV.AU



Table of Contents

1	General	3
1.1	Responsibilities	3
1.2	Cross references	3
1.3	Standards	3
1.4	Interpretation	4
1.5	Hierarchical road network	6
2	Pre-design planning	8
2.1	General	8
2.2	Planning	9
2.3	Consultation	10
3	Design	10
3.1	Design Domain	10
3.2	Road network Design criteria	10
3.3	Design parameters	11
3.4	Design speed	13
3.5	Cross-section	14
3.6	Sight distance	20
3.7	Coordination of horizontal and vertical alignment	21
3.8	Horizontal alignment	21
3.9	Vertical alignment	24
3.10	Auxiliary lanes	26
3.11	Intersections	26
3.12	Roundabouts	29
3.13	Traffic calming	29
3.14	Parking	31
4	Documentation	32
4.1	General	32
4.2	Drawings	33
4.3	Work-as-executed	35

1 General

1.1 Responsibilities

1.1.1 Objectives

General: Design and document a road system to provide the following:

- Improved urban structure and revitalisation.
- A safe, efficient, functional and economical road network, considering the volume, type and distribution of traffic that is appropriate to the existing built fabric and landforms, climate, heritage and cultural context of the area.
- Convenient and safe access for movement of pedestrians, vehicles and cyclists.
- Appropriate access for buses, emergency and service vehicles.
- A quality road network using integrated design that minimises maintenance costs.
- A convenient zone for public utilities, landscaping and street furniture, signals, signs and markings within the road reserve.
- Potential for expansion of the road network with minimum reconstruction by considering traffic growth and development nearby.
- Convenient parking.
- Street lighting.

1.2 Cross references

1.2.1 General

Requirement: Conform to the following worksection(s):

- *D02 Quality requirements for design.*

Related worksections: The following worksections are related to this worksection:

- *D01 Development and subdivision of land*
- *D04 Site regrading.*
- *D06 Pavement design.*
- *D07 Subsurface drainage (Design).*
- *D10 Pathways and cycleways.*
- *D08 Bridges and other structures.*
- *D09 Stormwater drainage (Design).*
- *D11 Control of erosion and sedimentation (Design).*

1.2.2 Workgroup

Construction – Roadways

Other Publications

Councils' Development Control Plans

Councils' Standard Drawings

Street Opening Conference "Guides and Practices for Street Openings"

Fire safety guideline Access for emergency vehicles and emergency service personal

1.3 Standards

1.3.1 General

Road design: To Austroads AGRD01 and Austroads AGRD02 Guidelines

Geometric design: To Austroads AGRD03 Guidelines

Intersection design: To Austroads AGRD04 and Austroads AGRD04A Guidelines

Traffic management: To Austroads AGTM series.

1.4 Interpretation

1.4.1 Abbreviations

General: For the purposes of this worksection the following abbreviations apply:

- AADT: Average Annual Daily Traffic.
- ASD: Approach Sight Distance.
- AU: Auxiliary.
- BA: Basic.
- CH: Channelised.
- DDA: Disability Discrimination Act
- EDD: Extended Design Domain.
- HOV: High occupancy vehicle.
- LATM: Local Area Traffic Management.
- MGSD: Minimum gap sight distance.
- NDD: Normal Design Domain.
- SISD: Safe Intersection Sight Distance.

1.4.2 Definitions

General: For the purpose of this worksection, the definitions given in Austroads AP-C87 and Austroads AGRD03 and the following apply:

The words 'street' and 'road' are interchangeable throughout all parts of this worksection.

- Activity centre: Urban planning term for those places that are vibrant hubs where people shop work, meet, relax and often live.
- Approach sight distance: Relates to the ability of drivers to observe the roadway layout at an anticipated approach speed.
- Batter:
 - The uniform side slope of walls, banks, cuttings, etc. Usually expressed as a ratio of horizontal to vertical.
 - The amount of such slope or rake, usually expressed as a ratio of horizontal to vertical, distinct from grade.
 - To form a uniform side slope to a wall, bank, or cutting.
- Carriageway: That portion of a road or bridge devoted particularly to the use of vehicles, that is between guide posts, nominal face of kerbs, or barriers, edge lines where these are provided, inclusive of auxiliary lanes, excluding shoulders.
- Crossfall: The slope of the surface of a carriageway measured normal to the design or road centreline.
- Cycleway: Portion of a road or footpath for the exclusive use of cyclists.
- Extended design domain (EDD): The design domain for the assessment of existing roads. EDD is a range of values below the lower bound of the NDD.
- Footpath (pathway): A public way reserved for the movement of pedestrians, motorised wheelchairs and personal mobility devices.

- Horizontal alignment: The bringing together of the straights and curves in the plan view of a carriageway. It is a series of tangents and curves that may or may not be connected by transition curves.
- Landform: The type and shape of terrain, usually including topography, geological characteristics, coastlines, rivers and water bodies.
- Length of superelevation development: The transition of crossfall from a normal roadway on straight alignment to that of a fully superelevated crossfall on a circular curve.
- Level of service: A qualitative measure describing operational conditions within a traffic stream such as speed and travel time, freedom to manoeuvre, traffic interruptions, comfort, convenience and safety and their perception by motorists and/or passengers.
- Legibility distance: The maximum distance that the various types of traffic control signs or devices can clearly be seen under normal operating conditions and where there is no restriction to the line of sight.
- Minimum gap sight distance: Critical acceptance gap that drivers are prepared to accept when undertaking a crossing or turning manoeuvre at intersections.
- Minor road: All roads which become part of the public road system and are supplementary to arterial and sub-arterial roads. Minor roads may include local sub-arterial roads, collector roads, local roads, and access streets. The terminology of road hierarchy may be different in different states. Refer to the relevant State Road Authorities for more information www.australia.gov.au/information-and-services/transport-and-regional/roads-and-road-transport/authorities
- Network: Defined as:
 - A connected system of roads and infrastructure that heavy vehicles can travel on. Can be restricted to a certain class(es) of heavy vehicles (NHVR).
 - Set of roads which provide a means of road based travel within a region. In transport terms it is defined in terms of links and nodes.
- Normal design domain (NDD): The design domain for a new road that defines the normal limits for the values of parameters that have traditionally been selected for new roads.
- Outer separator: The portion of the road reserve separating a through carriageway from a service road.
- Pathway: See footpath.
- Pavement: The portion of a carriageway placed above the subgrade for the support of, and to form a running surface for, vehicular traffic including subbase and base course.
- Plan transition: The length over which widening and shift is developed from the 'tangent-spiral' point to the 'spiral-curve' point; i.e. the length between the tangent and the curve.
- Reaction time: The time taken for a driver to perceive and react to a particular stimulus and take appropriate action. It is measured in seconds.
- Road network: A framework for movement by other modes, including pedestrian, bicycle and bus and plays a vital role in supporting neighbourhoods and town centres.
- Road reserve: The strip of public land between abutting property boundaries, specifically gazetted for the provision of public road and controlled by the definitions of the Roads Act (as per applicable State legislation). It includes the road carriageway, as well as footpaths, verges and landscape.

- Roundabout: A form of intersection channelisation in which traffic circulates clockwise around a central island and all entering traffic is required to give way to traffic on the circulating roadway.
- Safe intersection sight distance (SISD): Relates to an overall check that vehicles utilising the intersection have sufficient visibility to allow reaction and deceleration so as to provide adequate stopping distance in potential collision situations.
- Service road: A low traffic volume roadway parallel to and separated from an arterial road by an outer separator to limit vehicular access direct to the low volume road.
- Shoulder: The portion of formed and sealed carriageway that is adjacent to the traffic lanes and flush with the sealed surface of the pavement.
- Shoulder width: The measurement taken from the outer edge of the traffic lane to the edge of usable carriageway and excludes any berm, verge, rounding or extra width provided to accommodate guideposts and guard fencing.
- Side friction factor (f): A measure of the frictional force between the pavement and the vehicle tyre.
- Sight distance: The distance, measured along the carriageway, over which the visibility occurs between the driver and an object or between two drivers at specific heights above the carriageway in their lane of travel.
- Speed (85th percentile): The speed at or below which 85% of the vehicles travel:
 - Design speed: A speed fixed for the design and correlation of those geometric features of a carriageway that influence vehicle operation.
 - Desired speed: The speed over a section of a road adopted by a driver as influenced by the road geometry and other environmental factors.
 - Operating speed: The speed for an existing road at a time when traffic volumes are low and which allows a free choice of speed within the road alignment.
- Stopping sight distance: The sum of the braking distance and the distance the vehicle travels at a design speed during a reaction time of 2.5 seconds.
- Superelevation: A slope on a curved pavement selected to enhance forces assisting a vehicle to maintain a circular path.
- Traffic lane: That part of the roadway set aside for one-way movement of a single stream of vehicles.
- Traffic lane width: Traffic lanes are measured to the face of the kerb or to the lane line for multi-lane roads or roads with shoulders.
- Verge (rural): Defined area of the formation in rural roads outside the shoulder at the top of the batter slope.
- Verge (urban): That portion of the road formation not covered by the carriageway or footpath.
- Vertical alignment: The longitudinal profile along the centreline of a road consisting of series of grades and vertical curves.

1.5 Hierarchical road network

1.5.1 Road functions

Requirement: Design the network so that the predominant function of the road is conveyed to all road users. Each class of road in the network serves a distinct set of functions and a hierarchical road network is essential to maximise road safety, residential amenity and legibility.

Traffic management at network level: Conform to Austroads AGTM04.

Access management categories and overall road management: Conform to Austroads AGTM05.
Traffic management objectives: Conform to Austroads AGTM06.
Road function and traffic hierarchy: Conform to Austroads AGTM08.

1.5.2 Road classification

Terminology: The terminology used to describe each class of road varies from state to state. This worksection uses the functional categories common to the majority of states.

Levels of roads: The five generic distinct levels of roads are Access Road, Local Road, Collector Road, Sub-Arterial Road and Industrial Road.

Functional classification of urban roads: To Austroads AGRD02 Table 2.3.

Refer to Standard Drawings for road formation detail with regards to each equivalent level of council road classification.

Functional classification of rural roads: To Austroads AGRD02 Table 2.2.

Refer to Standard Drawings for road formation detail with regards to each equivalent level of council road classification. All Council rural roads would fall within Austroads Class 3, 4 or 5.

Note – All road reserve widths are minimum requirement. Additional width may be required to cater for cut and fill batters, catch drains, intersection layout requirements, adequate site distance, safe intersection site distance, special landscape requirements and provision for public utilities.

1.5.3 Emergency access

Requirement: Desirable to provide at least two access routes for emergency access for each street type in all subdivisions.

Traffic calming: Provide calming geometry to conform with Austroads AGTM08.

1.5.4 Access road

Road hierarchy: Lowest order road.

Identification:

Access road Type 1 – Option for semi urban development for lots greater than 2000m²,

Access road Type 2 - 15 lots maximum

Access road Type 3 - 7 lots maximum

Function: Residential with amenity features which facilitate pedestrian and cycle movements.

Vehicular traffic is compliant, in terms of speed and volume to amenities, pedestrians and cyclists.

Refer to Council Standard Drawings for minimum acceptable road design requirements

1.5.5 Local road

Road hierarchy: Second lowest order road.

Function: A local residential street, balancing the status of the street in terms of access with residential amenity functions. Resident safety and amenity are dominant but to a lesser degree than access streets. Typically, local streets link access streets with collector streets

Refer to Council Standard Drawings for minimum acceptable road design requirements

1.5.6 Collector road

Road hierarchy: Third lowest order road.

Function: Residential but also carries higher volumes of traffic collected from local streets and connects to local sub-arterial roads for community transport and business access. There is a reasonable level of residential amenity and safety through restrictions of traffic volumes and speeds.

However, amenity and resident safety do not have the same priority as in access streets or local streets.

Refer to Council Standard Drawings for minimum acceptable road design requirements

1.5.7 Sub-arterial road

Road hierarchy: Highest order road.

Function: Convenient and safe distribution of traffic generated by the development. It provides direct access for single dwelling allotments and access for multi-unit developments and non-residential land uses as appropriate.

Refer to Council Standard Drawings for minimum acceptable road design requirements

1.5.8 Industrial road

Identification: Industrial roads are of a higher construction standard due to their function.

Description: Industrial roads are provided in areas allowed for such development as shown in the relevant Development Control Plan and as determined by Council.

Refer to Council Standard Drawings for minimum acceptable road design requirements

1.5.9 Private roads / Accessways

In addition to the public road hierarchy there are 2 private road categories for residential developments.

Private Roads are roads owned by the owners of the land on which the road is located. A private road can either serve up to a maximum of three or six allotments or one community/strata titled development. Maintenance of these roads is the responsibility of the landowners and not Council.

Refer to Council Standard Drawings for minimum acceptable characteristics for a residential private road and design guideline parameters

Private roads within other types of developments will be considered at the time of the application.

2 Pre-design planning

2.1 General

2.1.1 Planning stages

General: Plan and design road network to Austroads AG RTP. Carry out the following planning studies:

- Need study: A study to identify the requirements for new or upgrading the existing road network.
- Reconnaissance study: A qualitative study to identify all possible routes and feasibility of each route.
- Corridor study: A quantitative and qualitative study to select the preferred route.
- Route study: A graphical development of plans for all possible location of routes of the proposed development.

2.1.2 Geometric design elements

General: The geometric road design comprises of the following at a minimum:

- Selection of the following road network elements to be incorporated in the design:
 - Existing road network shown

- Cross section (e.g. widths of lanes, shoulders, medians and verges).
- Horizontal curves.
- Vertical curves and gradients.
- Intersections.
- Merge/diverge areas.
- Long Sections
- Sight Distance
- Sizing of selected road network elements.
- Linking the road network elements into a three dimensional sequence.

2.2 Planning

2.2.1 Road hierarchy

Requirement:

- For new areas: Make sure each class of route reflects its role in the road hierarchy by its visual appearance and physical design and is distinct from established areas with a pre-existing road pattern.
- Functional classification: Routes differ in alignment and design according to the volume of traffic they are intended to carry, the desirable traffic speed, and other relevant factors. Most road authorities have developed a functional hierarchy.

2.2.2 Integrated design principles

Requirement: Integrate design principles in the development of the road network to improve operational efficiency, road safety, public amenities while minimizing environmental impacts of noise, vibration and pollution.

Requirement: Consider the following in integrated design planning:

- Transport and community needs.
- Integrate natural patterns and design in response to topography and landform.
- Design roads so that their appearance signifies their function and their intended speed posting.
- Improve the legibility.
- Provide a self-reliant and minimal maintenance natural landscape.
- Integrate noise control in road network design.
- Avoid adverse visual impacts

Preparation for design: For design development inputs conform to Austroads AGRD08.

2.2.3 Conformance with Development Control Plan

Pattern and width: Conform to any relevant Development Control Plan (DCP). In areas not covered by such a plan, pattern and width(s) are determined by Council.

2.2.4 Legibility

General: Design for clear legibility in conformance with the following:

- Differentiation: Reinforce legibility by providing sufficient differentiation between the road functions.
- Landmark features: Emphasise distinct landmark features such as watercourses, mature vegetation or ridge lines within the structural layout so as to enhance the legibility.

- Introduced features: Provide the necessary legibility, by the inherent design and functional distinction of the road network in addition to introduced physical features such as pavement and lighting details

2.3 Consultation

2.3.1 Council and other authorities

Council consultation: Before starting design, liaise with the Council's officer(s) for the following:

- Roadway layout and traffic management.
- Stormwater and subsurface drainage.
- Landscaping.

Other authorities: Consult with and seek approval for the development from the following government authorities:

- State roads authority.
- State and local planning authorities.
- State and federal environmental agencies.
- Rail authorities if the proposed project crosses the rail network.
- Regional catchment management authority.
- Water authorities.
- Other utility authorities.

2.3.2 Public consultation

Requirements: Public consultation on design proposals shall be provided where such action is required as part of Council policy.

2.3.3 Utilities service plans

Existing services in the development area/precinct: Liaise with the utility authorities affected by the scheme and if required, obtain service plans from the authorities of the proposed development area for above ground and below ground services.

Requirements for utility services: To SOCC.

Utility services location: To AS 5488.1 and AS 5488.2. Contact DIAL BEFORE YOU DIG to identify the locations of underground utility services pipes and cables.

3 Design

3.1 Design Domain

Design domain to AGRD02 clause 2: Apply NDD (Normal Design Domain) according to the following:
– New construction, significant lengths of reconstruction of existing roads, new carriageway of a duplication.

3.1.1 Location

Road network location: The design requirements of urban and rural roads differ in relation to operating speeds, abutting access, geometry and cross-section.

3.2 Road network Design criteria

3.2.1 Routing

General: Provide routing as follows:

- Avoid through routes in the internal road system that are more convenient than the external road network in conformance with Austroads AGTM04 and Austroads AGTM08.
- Design and locate the external road network to provide routes that are more convenient for potential through traffic within the network.
- Provide access to major roads at intervals of no more than 1.5 km, of adequate capacity to accommodate through network movements.

3.2.2 Road links

General: Provide for road links as follows:

- Hierarchy: Except in exceptional circumstances, do not link one road with another that is more than two levels higher or lower in the hierarchy.
- Restriction: Avoid access from Access streets or Local streets to an access-controlled arterial road.

3.2.3 Traffic flow

Traffic flow and speeds: Make sure that the traffic design for flow and speeds on any road are compatible with the residential functions of that road.

Traffic management in Activity centers: Conform to Austroads AGTM07.

Traffic impacts assessment: Conform to Austroads AGTM12 clause 4. Refer also to *D01 Development and Subdivision of Land*

3.2.4 Transport provisions

Road layout: Conform to the requirements of the external road network and satisfy the transport provisions of an outline development plan.

Travel time: Minimise the time required for drivers to travel on all streets within the development.

Internal road connections: Provide intersections of internal roads as T-junctions or controlled by roundabouts.

Local sub-arterial road: Minimise the length of local sub-arterial road within a development.

Access street: Restrict the maximum length of an Access street so that its status as a residential place is retained. Adopt design speed and volume to allow the integration of pedestrian, bicycle and vehicular movements without impairing residential convenience.

Pedestrian or bicycle network: Where Access streets form part of a pedestrian or bicycle network, provide for access links with adjoining access streets or open space systems for functional efficiency of the pedestrian and bicycle network.

3.3 Design parameters

3.3.1 Location

Road network location: Select urban or rural.

3.3.2 Traffic volume and composition

Requirements: Determine the following traffic characteristics to Austroads AGTM03.

- Traffic volume: Determine the volume of traffic to be carried by the road by conducting traffic studies and surveys to Austroads AGTM03.
- Make allowance for traffic growth, commensurate with pavement design life e.g. 40 years
- Roadway capacity.
- Level of service.

- Roadway conditions: Affect the roadway capacity and level of service depending on type of road and environment, traffic lane and shoulder widths, design speed, horizontal and vertical alignment.
- Terrain conditions: Generally classified as level, rolling and mountainous.
- Traffic composition: Generally classified as passenger cars, trucks and buses.
- Vehicle characteristics: Vehicle types and length or axle configurations.

Traffic lanes: Capacity analysis, level of service and design traffic volumes are used to determine the number of traffic lanes required.

3.3.3 Road classification

Requirement: Determine the functional road classification of the network to be designed in conformance to the **Hierarchical road network**.

3.3.4 Vulnerable road users

Pedestrians, cyclist and motorcyclists: Provide safe and convenient passage to vulnerable road users to Austroads AGRD03 clause 2.2.4 and Table 2.1.

3.3.5 Design speed and operating speed

Requirement: Identify the operating speed for existing roads and select the design speed for both existing and planned lengths of the road.

3.3.6 Alignment controls

Requirement: Identify any mandatory and discretionary controls for the proposed alignment.

3.3.7 Design vehicle

Requirement: Determine the type of vehicles that will be operating on the road network to establish the traffic lane widths, road geometry and intersection layout eg garbage trucks, buses, delivery trucks.

3.3.8 Use of roads as emergency aircraft runway strip

Requirement: In an emergency in remote areas, roads may be designed to operate as emergency aircraft runway strips to Austroads AGRD03 Appendix B.

3.3.9 Environmental considerations

Requirement: Evaluate the environmental considerations including topography, existing public utility services, visual intrusion, noise, vibration and pollution in the road design to Austroads AGRD03 clause 2.2.9.

Noise reduction: Consider vertical alignment adjacent to intersections and/or sensitive areas (e.g. schools, hospitals) to minimize braking noise.

Salinity prevention: For the design of roads through or adjacent to land known to be salt affected, take the following actions:

- Consultation: Consult with the relevant land and water resource authority.
- Early planning: Consider adjustments in horizontal and vertical line to avoid detrimental interference to and recharge of subsurface water within or adjacent to the road reserve.
- Landscaping: Select appropriate native deep-rooted species for plantings in association with road reserve works. Provide for plantations of sufficient size and density, multiple row belts and relatively close spacings, to lower the groundwater table.

3.3.10 Heritage considerations

Requirement: Plan for the management of heritage assets. Heritage sites are recorded in the State heritage asset register. Some sites may contain archaeological sites relating to Aboriginal or non-Aboriginal occupation.

3.3.11 Access management

Requirement: Provide safe and appropriate access for the movement of traffic between the proposed road and the adjacent land.

3.3.12 Drainage

Drainage methods: Select the appropriate drainage methods to the *D07 Subsurface drainage (Design)* and *D09 Stormwater drainage (Design)*.

3.3.13 Utility services

Location: Locate the utility services in the road reserves such that there is minimum service relocations in case of future upgrades or growth in or around the proposed development.

3.3.14 Topography

Site specific features: Design the road with the terrain rather than against it and carry out the geotechnical investigation of the site to Austroads AGRD07.

3.4 Design speed

3.4.1 General

Design parameters: Use design speed as the basic parameter in road design as it is dependent on the functional classification of the road, topography, land use and abutting development and desired speed of drivers.

3.4.2 Operating speed on urban roads

Requirement: Conform to the following:

- Speed limits: To Austroads AGTM05 Table 5.4.
- Typical urban operating speeds: To Austroads AGRD03 Table 3.1.

3.4.3 Operating speed on rural roads

Criteria: Determine the minimum design speed value for other elements for Council Works on the concept of a speed environment as outlined in Austroads AGRD03 clause 3.4.

Restricted access to major roads: Design all rural subdivisions to control access to major roads. Limit access to one point on to local, collector, local sub-arterial or arterial road networks.

3.4.4 Desired speed

Existing rural roads: For restoration projects on existing rural roads, measure the operating speed from the suitable section of the existing road. Measure the desired speed directly as the 85th percentile speed on long straights. Also account for any increase in operating speed due to improved cross section and ride quality.

New rural roads: Select the desired speed from Austroads AGRD03 Table 3.3.

3.4.5 Operating speed model

Model: Determine the operating speed using the operating speed model to Austroads AGRD03 clause 3.6 to predict the operating speed of cars along the length of the road.

3.4.6 Vehicle speed

Requirement: Determine the acceptable vehicle speed for the particular section of road to Austroads AGRD03 clause 3.2.5.

3.4.7 Operating speed for temporary works

Requirement: Determine the operating speed for temporary roads to Austroads AGRD03 clause 3.8.

3.4.8 Hazard reduction

Low speeds: Adopt a low design speed to discourage speeding. Avoid vertical or horizontal curves on low design speed roads to minimise the risk of creating a potentially dangerous section of road.

Hazardous features: Make hazardous features visible to the driver. Adopt traffic engineering measures that help a driver avoid errors of judgement.

Road safety barriers: Assess and design road safety barriers to AS/NZS 3845.1.

3.4.9 Rural road design

This section specifically applies to sites greater than one hectare and where permissible for rural developments, excluding homes and ancillary structures. Where subdivision is being undertaken, existing unsealed roads fronting the subdivision shall be upgraded and sealed in accordance with *D06 Pavement Design* and Councils' standard drawings unless council determines otherwise.

Carriageway width for Rural Roads: Carriageway and shoulder width shall comply with Councils Standard Drawing.

All rural subdivisions creating lots less than 2 Ha shall be designed to deny property access to local sub-arterial roads.

Gates are to be recessed within the property a minimum of 6 metres from the road frontage.

Superelevation: Where appropriate, superelevation, widening, centerline shift and their associated transitions are to be incorporated into the road design. At low and intermediate ranges of design speed (below 80Km/Hr) it is desirable to superelevate all curves at least to a value equal to the normal crossfall of straights.

3.5 Cross-section

3.5.1 Road reserve characteristics

Cross section: Provide for all road functions including the following:

- Safe and efficient movement of all users (including emergency vehicles and operation of buses on connector streets)
- Provision for parked vehicles. Give particular attention to access for disabled persons in conformance with the *AUS Gov Act No. 135 - Disability Discrimination Act 1992*.
- Access to public transport.
- Buffer from traffic acoustic nuisance for residents.
- Provision of public utilities and WSUD devices.
- Streetscaping.
- Requirements of *AUS Gov Act No. 135 - Disability Discrimination Act 1992*.
- Operational aspects: Conform to the following:
- Allow vehicles to proceed safely at the operating speed intended for that level of road in the network with only minor delays in the peak period.
- Take into consideration the restrictions caused by parked vehicles where it is intended or likely that this will occur on the carriageway.

- Vehicles include trucks, emergency vehicles and buses, on some roads. (Refer to **Bus route criteria table**).

Design life: To Austroads AGRD01 Table 3.1.

3.5.2 Type of cross-section

General: Determine the type of cross-section considering the following factors:

Location: Urban or rural.

Function of the road: Through route or local access.

Type of road: New or existing.

Traffic volume: Expected traffic volume in AADT.

Public transport: Provisions for public transport and frequent stopping.

Environmental constraints: Environmental factors like topography, existing public utilities, existing road reserve widths, vegetation and geology.

Availability of construction materials: For example: Bituminous sprayed seal, asphalt, concrete or any other suitable pavement material.

Design life: To AGRD03 Table 4.1.

3.5.3 Traffic lanes

General: Determine the number and width of the traffic lanes required depending upon the traffic volume, presence of cyclists, available road reserve width and the side friction constrained by abutting access.

Standard traffic lane width for urban and rural roads: 3.5 m.

Reduced lane width: If there are site constraints the traffic lane width may be reduced to 3.2 m subject to the approval of the relevant road authority.

Urban arterial road widths: To Austroads AGRD03 Table 4.3.

Single carriageway rural road widths: To Austroads AGRD03 Table 4.5.

Divided carriageway rural road widths: To Austroads AGRD03 Table 4.6.

Pedestrians and cyclists: Provide for the safety of pedestrians and cyclists where it is intended they use the carriageway by providing sufficient width and control of landscaping to provide sight distances.

3.5.4 Crossfall

Pavement crossfalls: Crown the roads on centreline. Provide crossfall to drain the carriageway on straights and curves and to provide superelevation on horizontal curves.

Pavement crossfall on straights: To Austroads AGRD03 Table 4.2

Recommended minimum crossfall: 2%. Recommended maximum crossfall 4%

Offset crown lines: In urban areas there are many factors that force departure from the recommended crossfalls. The difference in level between the road alignments can be taken by offsetting crown lines or by adopting one way crossfall. Adopt sustained crossfalls with a minimum of 4% and a maximum of 6%.

Rate of change: Do not exceed the rate of change of crossfall in the following conditions:

- Through traffic: 6% per 30 m.
- Free flowing turning movements: 8% per 30 m.
- Turning movements for which all vehicles are required to stop: 12% per 30 m.

Precedence of crossfall over grade: Conform to the following:

- The crossfall on a Collector street or Local sub-arterial road will take precedence over the grade in Local or Access streets. Maintain the crossfall on the major road and adjust the local street levels to suit.

- A rate of change of grade of 2% in the kerb line of the side street relative to the centre line grading is a reasonable level.

3.5.5 Shoulders

Function: Design road shoulders to carry out the following functions:

- Structural: Provide lateral support to the road pavement layers.
- Traffic: Provide an initial recovery for an errant vehicle, emergency use, a refuge for stopped vehicles and space for cyclists.

Shoulder width: Provide the following:

- Generally: 1.5 – 2 m.
- For higher volume roads: 2.5 – 3 m.

Shoulder sealing: Seal the shoulders partially or wholly to reduce maintenance costs and to improve moisture conditions under pavements. Seal shoulder where longitudinal gradient exceeds 5% to avoid erosion. Conform to the following sealed widths:

- Minimum width of shoulder seal for AADT < 1000: 0.5 m.
- For wet areas where moisture control is required:
 - Desirable shoulder seal width: 0.5 m.
 - Preferred shoulder seal width: 1 m.
- For discretionary stopping of cars: 2.5 m.
- For bicycles, minimum sealed width: 2 – 3 m.

Shoulder crossfall: Provide shoulder crossfall to Austroads AGRD03 clause 4.3.5.

3.5.6 Verge

General: Design the verge to perform the following functions:

- A traversable transition between the shoulder and the batter slopes.
- A firm surface for stopped vehicles.
- Space for installation of guideposts and road safety barriers.
- Reduce scouring due to stormwater run-off.

Minimum width: To Austroads AGRD03 Table 4.9.

Verge rounding: Provide verge and batter toe rounding to minimise rollover accidents to Austroads AGRD03 Table 4.10.

Verge slope: Provide verge slopes for local roads or behind kerb and gutter in cut:

- Without rounding: 5%.
- With rounding: Initial slope same as abutting shoulder.

3.5.7 Verges and property access

Criteria: Design the verge with consideration of utility services, the footpath width, access to adjoining properties, likely pedestrian usage and preservation of trees.

Restriction: If normal crossfalls are impracticable adopt low level footpaths.

Desirable Crossfall in footpath paving: 2.5% as per Austroads AGRD06A.

Longitudinal grade: Conform to the following:

- Maximum longitudinal grade of 5%.

Driveway profile: Conform to the following:

- Provide a vehicular driveway centreline profile for the property access, in accordance with Councils standard drawing where applicable.

- Check the design using critical car templates (B85 for residential driveway and B99 for commercial/Multi Unit / Public Driveways) in accordance with Australian Standard AS 2890
- Design driveway profiles so that vehicles can use the driveway satisfactorily.

3.5.8 Batters

Requirement: Accommodate differences in level across the road between road reserve boundaries by the following measures used individually or combined:

- Cutting at the boundary on the high side and providing the verge at normal level and crossfall.
- Battering at the boundary over half the verge width with the half against the kerb constructed at standard crossfall.

Batter slopes: Design the batter slopes considering the following factors:

- Recommendations of geotechnical investigations.
- Batter stability and safety.
- Recovery of errant vehicles requires a maximum batter slope of 4:1
- Available width of road reserve.
- Landscape requirements.
- Maintenance costs and accessibility requirements. Maximum Preferred maximum batter slope for a slasher is 4:1.

Batter slopes: To Austroads AGRD03 Table 4.11.

Benches: Provide benches for high batters > 10 m vertical height or batters on unstable ground. Provide benches as shown in Austroads AGRD03 Figure 4.14.

- Minimum width of bench: 3 m.
- Maximum crossfall: 10%.
- Preferred bench width for road safety, maintenance and drainage: 5 m.

3.5.9 Roadside drainage

General: Provide appropriate drains to remove water from the road and its surroundings and to maintain road safety and pavement strength to Austroads AGRD03 clause 4.6.

- Table drain: Provide a dish drain, or similar structure along the invert of table drains, seal the outer edges of the pavement, the shoulder verges and the drain lining where scour is likely to occur to Austroads AGRD03 Figure 4.16. Provide the following slopes:
 - Side slopes: < 4H:1V.
 - Desirable slope: 6H:1V.
- Catch drains: Provide catch drains to prevent overloading of the table drain and scour of the batter face at least 2 m from the edge of cuttings to minimise possible undercutting of the top of the batter.
- Median drains: Provide median drains with side slopes 10H:1V to reduce the chance of vehicle overturning. Provide a depressed median of minimum 10 m width. Place the invert of the median drain below subgrade level to facilitate drainage of pavement layers.
- Kerb and Gutter: Provide Kerb and Gutter to perform the following:
 - Collect and convey surface drainage to a discharge point.
 - Delineate the edges of the carriageway.
 - Separate carriageways from areas dedicated to footpath users.
 - Support the edge of the base course of the pavement.

- Reduce the width of cut by substituting an underground drainage system in place of table drains.
- Kerb & Gutter type: Select the kerb & Gutter type from the following:
 - Reinforced Dish Crossing
 - Standard Kerb & Gutter
 - Rolled Kerb & Gutter
 - Low Flow V drain
 - Raised median & traffic Island
 - Gutter adjacent to cuttings
- Kerb placement: Conform to the following:
 - Provide Standard kerb & Gutter for lightly trafficked Local roads, adjacent to parking lanes and parking areas and bus bays to reduce the risk to pedestrians.
 - Provide layback/rolled kerb on minor roads to allow for off-road parking and for continuous access to property.
- Kerb location: Place Kerb and Gutter with the clearance between the face of the kerb and edge of the traffic lane to Austroads AGRD03 Table 4.14.

3.5.10 Scour protection

Requirement: Provide scour protection of roadside drainage and table drains depending on the nature of the soils, road gradients and volume of stormwater runoff.

Protection of the works: Provide concrete lined channels, turfing, rock pitching, grass seeding, individually or in combination. Carry out geotechnical investigations to determine the level and extent of any protection works before proceeding to final design stage.

3.5.11 Medians

General: Provide medians to improve the safety and operation of urban and rural roads with multiple lanes.

Median type: Select raised or depressed type to Austroads AGRD03 Figure 4.21.

Median width: Minimum urban median width to Austroads AGRD03 Table 4.15.

Median slopes: Provide median slopes to Austroads AGRD03 Table 4.16.

Median transitions: Provide appropriate transition to safely merge and diverge vehicles to Austroads AGRD03 Figure 4.25.

Median, islands and kerb blisters are to be painted with white reflective (glass beads) paint and appropriate “keep left” signs

3.5.12 Public pathways, footpaths and cycleways

Requirement: In accordance with Council’s Standard Drawings

3.5.13 Bicycle lanes

General: Consider provisions for cyclists in the road design to Austroads AGRD03 clause 4.8 and provide adequate space for cyclists to share the road safely and comfortably by providing on-road bicycle facilities in the form of the following:

- Separate bicycle lanes: Provide separation from other motor traffic with exclusive bicycle lane on the left side of the road by pavement markings and signs.
- Road shoulders.
- Widened lanes for joint use by bicycles and other vehicles.

Bicycle lane width: To Austroads AGRD03 Table 4.18.

Restriction: Provide a minimum bicycle width of 2 m in congested areas.

Minimum clearance with adjacent traffic on local roads: 1 m.

Reference: Councils Bicycle Strategy

3.5.14 High occupancy vehicle (HOV) lanes

General: If there are any public transport services proposed in the route, provide HOV priority lanes for public transport in conformance with the following:

- Shoulder width: 3.5 m.
- Intermittent bays: Provide bays with appropriate length tapers to provide safe movement of vehicles.
- Provide access to public transport in conformance with the AUS Gov Act No. 135 - Disability Discrimination Act 1992.

Bus lane width: On new roads, conform to the following:

- To Austroads AGRD03 Table 4.22.
- Minimum width between the kerbs:
 - If bicycle lanes are provided: 15 m.
 - If bicycle lanes are not provided: 11.6 m.
- Width of kerbside bus lanes: To Austroads AGRD03 Table 4.23.

3.5.15 Service roads and footpath

General: Provide service roads for access to the abutting property or control access to the arterial road from the abutting property.

Minimum service road lane width: To Austroads AGRD03 Table 4.26.

Access to allotments: Adopt a carriageway width to provide for unobstructed access to individual allotments. Provide for drivers to comfortably enter or reverse from an allotment in a single movement, taking into consideration the possibility of a vehicle being parked on the carriageway opposite the driveway.

Minimum service road carriageway width for roads with low traffic volumes: To Austroads AGRD03 Table 4.27.

Operating speed: 40 to 60 km/h.

Outer separator width: To Austroads AGRD03 Table 4.28.

Urban border: Consider urban borders comprising a pedestrian path and nature strip to Austroads AGRD03 Table 4.28.

Typical urban border slopes: Conform to the following:

- For footpaths:
 - Desirable: 1%.
 - Maximum: 2.5%.
- Nature strip:
 - Grassed soil: 4 to 10%.
- Determine minimum slope on urban borders by considering the drainage.
- Determine the maximum slope by considering the terrain and provision of access at driveways.

Footpaths: Provide footpaths either adjacent to the roadway or separated from it by a nature strip.

- Standard: To Austroads AGRD06A.
- Minimum desirable width: 1.2 m.

- Crossfall: Varies from flat to 2.5%.

3.5.16 Bus stops

New bus stops: Bus routes will normally be identified by Council. It is important that the road hierarchy adequately caters for buses. Construction to be in conformance with the requirements of the Disability Discrimination Act (Australian government 1992) and other road authorities and transport agency disability standards which outline the requirements of the access paths, manoeuvring areas, ramps, waiting areas, surfaces and tactile ground surface indicators.

Urban bus stops: To Austroads AGRD03 Figure 4.51.

Rural bus stops: Locate bus stops in the road shoulder between the carriageway and table drain.

Minimum shoulder width for a bus stopping area: 3 m.

Minimum length of bus stopping area: 15 m.

For intermediate speed environments provide a longer sealed distance: 30-50 m.

3.5.17 Street name signs

Street name blades, brackets and posts shall be provided at all street junctions, intersections and roundabouts, in accordance with Councils' standard drawings.

3.5.18 Vehicular crossings

Kerb layback crossings in accordance with Councils' standard drawings

3.6 Sight distance

3.6.1 General

Stopping and sight distance: Provide stopping and sight distance at all points on the road conforming to Austroads AGRD03 Clause 5 and AS2890.1.

3.6.2 Sight distance parameters

General: To Austroads AGRD03 Table 5.1 and the following:

- Driver reaction time: Adopt reaction time of 2.5 seconds for all roads. If 1.5 seconds and 2 seconds reaction times are required, arrange approvals from the State Road Authority.

3.6.3 Stopping sight distance

General: Conform to the following:

- General: To Austroads AGRD03 clause 5.3, measured from an eye height of 1.15 m to an object height of 0.20 m.
- On sealed roads: Car stopping sight distance to Austroads AGRD03 Table 5.5.

3.6.4 Sight distance on horizontal curves

General: Conform to the following:

- On horizontal curves: To Austroads AGRD03 Figure 5.4 which shows the relationship between horizontal sight distance, curve radius and lateral clearance to the obstruction.
- On horizontal curves with roadside barriers: Provide minimum shoulder widths and manoeuvre times for sight Austroads AGRD03 Table 5.7.

Horizontal curve perception sight distance: Provide sufficient sight distance by adopting larger crests for a horizontal curve. Do not provide a horizontal curve starting over a crest. Check sufficient visibility is provided for the curve by providing:

- Clear driver eye height: 1.1 m.
- A zero object height such that the driver can see the road surface in order to perceive the curvature.

- Driver visibility of a minimum of:
 - 5 degrees of arc.
 - 80 m of arc.
 - The whole curve.

3.7 Coordination of horizontal and vertical alignment

3.7.1 Horizontal and vertical alignment coordination

General: Consider 3 dimensional coordination of the horizontal and the vertical alignment of the road to increase efficiency, safety, encourage uniform speed, improve aesthetics and provide harmony with the landform and drainage.

Requirement: Conform to the following:

- Avoid the use of minimum radius horizontal curves with crest vertical curves.
- Contain the crest vertical curves within horizontal curves to enhance the appearance of the crest by reducing the three dimensional rate of change of direction and to improve safety.
- Provide the same design speed of the road in both horizontal and vertical planes.
- Avoid sharp horizontal curves at or near the top of a crest vertical curve.
- Consider three dimensional combined horizontal and vertical stopping sight distance and minimum sight distance.
- Provide a horizontal curve to indicate the change in direction before introduction of vertical curve in both directions of travel.
- Be aware that a short vertical curve on a long horizontal curve or a short tangent in the grade-line between sag curves may adversely affect the road's symmetry and appearance.
- Aesthetic consideration: Conform to the following:
- Provide horizontal curves slightly longer than the vertical curve, so that the curves fits with the terrain and are coincident.
- Provide long horizontal curves to short curves so that:
 - The overtaking opportunities are not reduced.
 - Small deflection angles avoid the appearance of a kink.
 - Best appearance is provided for deviations around obstructions.
 - The far tangent point is beyond the driver's point of concentrated vision for curves located at the end of long straights.

Drainage consideration: To ensure pavement drainage and to reduce the risk of aquaplaning, avoid very long crest and sag curves, that result in long sections of flat grades at the top and the bottom of the curves.

3.8 Horizontal alignment

3.8.1 General

Requirement: Provide horizontal alignment for safe and continuous vehicle operation at a uniform travel speed including the following:

- For low and intermediate speed rural roads and minor urban roads, where it is difficult to overcome the physical restrictions of curve radii, introduce curvature of a lower standard than the design speed of the project to Austroads AGRD03 Table 7.1.
- Provide tangents of suitable length as frequently as the terrain permits to facilitate overtaking manoeuvres.

- Determine the horizontal alignment from the design speeds for a particular street within the road hierarchy (see **Design Speed**).

3.8.2 Horizontal curves

Types of horizontal curves: Conform to the following:

- Compound curves: Provide a smaller curve preceding a larger curve. Avoid diminishing radii at steep downgrades.
- Reverse curves: Do not use reverse curves unless there is sufficient distance between the curves to introduce full superelevation of the two curves without exceeding the standard rate of change of crossfall for a particular design speed.
- Transition curves: Introduce transition curves to join the straight and circular curves to provide smooth travel of vehicles within the traffic lane.
 - Transition the horizontal curves with the transition length based on the superelevation runoff length for the recommended combination of speed, radius and superelevation.
 - Avoid transition curves for large radius horizontal curves and where operating speed is less than 60 km/h.
 - Provide transition paths for trucks, where lane width is no more than 3.5 m.

3.8.3 Horizontal curves and tangent lengths

Speed/radius relation: Conform to the following:

- For a given design speed, utilise the minimum radius of curvature that drivers can safely negotiate.
- Avoid curves that progressively tighten (e.g. parabolic curves) and sudden reverse curves that drivers cannot anticipate as they have the potential to produce an uncomfortable sense of disorientation and alarm.

Speed restriction: Where speed restriction is provided by curves in a street, conform to the relationship between the radius of the curve and the desired vehicle speed.

Tangents: Determine appropriate lengths for tangents between speed restrictions, which may be curves, narrow sections or other obstructions.

Sight distance: Determine the sight distance on curves to Austroads AGRD03 clause 5.4.

3.8.4 Side friction and minimum curve size

Recommended side friction factors: To Austroads AGRD03 Table 7.5.

Minimum radii for horizontal curves based on superelevation and side friction: To Austroads AGRD03 Table 7.6.

Maximum allowable deflection angles without horizontal curves: To Austroads AGRD03 Table 7.7.

3.8.5 Superelevation

Criteria: Determine the superelevation by considering the following:

- Operating speed of the curve.
- Difference between the inner and outer formation levels in flat or urban areas.
- Stability of high vehicles when adverse crossfall is considered.
- Length available to introduce the necessary superelevation.

Minimum radius of curves: Determine from the following:

- Design speed.
- Minimum superelevation (or maximum adverse crossfall) at any point on the circular portion of the curve.

Low design speed and crowned pavement: Conform to the following:

- Access and Local streets: For design speeds of 50 km/h or less, and curves of 60 m radius or less, generally crown the pavement on a curve instead of superelevation.

Superelevation in rural roads: Design superelevation, widening and centreline shift and transitions in conformance with the Austroads AGRD03 clause 7.7.

High design speed: Conform to the following:

- Maximum superelevation for urban roads of higher design speeds: 6%.
- Maximum values of superelevation for different road types: To Austroads AGRD03 Table 7.8.
- Avoid any increase in the longitudinal grade leading to excessive crossfall at intersections.
- While it is desirable to superelevate all curves, limit adverse crossfall to 3%.

Length of superelevation development: Design superelevation development lengths to satisfy both rate of rotation and relative grade criteria to Austroads AGRD03 Table 7.9.

3.8.6 Plan transitions

Transitions: Conform to the following:

- Planning: Plan transitions on superelevated curves for appearance and to provide sufficient length in which to apply the superelevation.
- Urban roads: Superelevation may be applied to the road cross section by shifting the crown to 2 m from the outer kerb, as long as the road is not too wide.
- Access to adjacent properties: The axis of rotation of the cross section for urban roads is normally the kerb grading on either side which best allows access to adjacent properties and intersections.
- On the outside of superelevation, or where the longitudinal grade of the gutter is < 0.5%, adopt a crossfall of 63 mm in a 450 mm wide gutter.

Restrictions: In urban road design it is often impracticable to use plan transitions as kerb lines are fixed in plan and any shift requires carriageway widening. Widening on horizontal curves compensates for differential tracking of front and rear wheels of vehicles, overhang of vehicles, and transition paths. If proposed roads are curved, consider the adequacy of carriageway width.

Crossfall changes: Avoid abrupt changes in crossfall, which can cause discomfort in travel and create a visible kink in the kerb line. Conform to the following:

- The wider the pavement the longer the transition.
- Use superelevation transitions at all changes in crossfall, not just for curves. Drainage problems can arise with superelevation transitions which may require extra gully pits and steeper gutter crossfalls.
- Where crossfalls change at intersections, draw profiles of the kerb line. Calculated points can be adjusted to present a smooth curve.

3.8.7 Curves with adverse crossfall

General: Avoid adverse crossfall greater than 3% except for curves with an operating speed of no more than 70 km/h in constrained areas and for intersection turns and roundabouts.

Minimum radii with adverse crossfall: To Austroads AGRD03 Table 7.12.

Adverse superelevation: Provide adverse superelevation at the following:

- Property access controls.
- Channel drainage controls.
- Grading restrictions.
- Intersections to maintain visibility of the road surface.

3.8.8 Pavement widening on horizontal curves

Widening: Provide pavement widening on curves to Austroads AGRD03 Table 7.13 to maintain lateral clearance between vehicles taking into account the following factors:

- Radius of the curve.
- Width of lane on a straight road.
- Vehicle length and width.
- Vehicle clearance.

3.9 Vertical alignment

3.9.1 General

Documentation: Show vertical alignment on a longitudinal section with a vertical scale of 10H:1V.

3.9.2 Vertical controls

Requirement: Consider the effect of the following features on the vertical geometric design:

- Existing topography.
- Geotechnical conditions.
- Existing intersections.
- Property entrances.
- Pedestrian access.
- Service utility assets.
- Median openings.

Minimum clearance above flood levels and water tables: As defined by the relevant road authority.

3.9.3 Vertical clearances

General: Provide minimum vertical clearances over roadways and pedestrian/cycle paths to Austroads AGRD03 Table 8.1.

Precedence: If there is a conflict, the following order takes precedence:

- Policies of the road owning authority, e.g. Council, State Road Authority.
- Requirements of the authority that owns the asset, e.g. rail authority.

3.9.4 Underground services

Clearance requirements: Consult the relevant authority to determine the minimum clearance requirements for:

- Gas mains.
- Water mains.
- Stormwater drains.
- Sewer outfall.
- Telecommunication cables.
- Underground electrical cables.
- Road authority assets, e.g. traffic signals and street lighting.

3.9.5 Longitudinal gradient

General: Provide grades as flat as possible, consistent with longitudinal drainage requirements so that all vehicles operate at the same speed. Conform to the following minimum grades:

- Road with kerb and Gutter:

- Minimum desirable grade: 1%.
- Absolute minimum grade: 0.3%.
- Roads in cut:
 - Unlined drains: 0.5%.
 - Lined drains: 0.3%.
- Roads without kerb and Gutter and not in cut: 0%.
- Minimum gradient of 0.5%.
- In very flat conditions: Reduce grade to 0.3%.
- If underground drainage with gully pits or other special works are used, consider near level grades. Provide variable crossfall to achieve the required grade in the gutter.

Maximum grade: To Austroads AGRD03 Table 8.3.

- Intersections: Conform to the following:
 - Longitudinal grade of the minor street on the approach to an intersection: < 4%.
 - Design actual gradient dependent on the type of terrain.
 - Interrelate the design of the road alignments and the grades used.
 - Avoid a steep grade on a minor side street if vehicles have to stand waiting for traffic in the major road.

Maximum grade in cul-de-sacs and turning circles: < 6 %.

Maximum gradientturning s for residential and rural subdivisions roads:

	Desirable maximum percentage	Absolute maximum percentage
Access Street:	12	16
Local Road	12	16
Collector Street:	10	12
Sub-arterial Road:	8	10
Rural Road:	10	12

Maximum grade over long lengths of road: To AGRD03 Table 8.3. In general, the maximum gradient will be based on level of service and quality of service considerations. The grades shown in AGRD03 table 8.3, which shows the maximum grades over long lengths of road in various terrain types, can be modified as appropriate by the severity of the terrain and the importance of the road.

3.9.6 Vertical curves

Criteria: Design vertical curves in conformance with the following:

- Provide vertical curves like simple parabolas on all changes of grade exceeding 1%.
- Desirable minimum design speed: 40 km/h.
- The length of the crest vertical curve for Stopping Sight Distance: To Austroads AGRD03 Table 8.7.
- Limit the length of crest curve with 0.3% to 0.5% grade: 30 to 50 m.

Sag curves: Provide the lengths of sag vertical curves to Austroads AGRD03 clause 8.6.4 and the following:

- For kerbed roads: Limit the maximum length of sag curves with less than 0.3% grade to 30 m.
- Maintain a minimum grade of 0.5% in the kerb and gutter by warping of road cross sections at sag points.

- Make provisions for draining both the road surface and the subgrade.
- To minimise discomfort due to rapid changes in vertical acceleration when passing from one grade to another, limit the vertical acceleration generated on the vertical curve to the following:
 - For desirable riding comfort: 0.05 g.
 - For minimum riding comfort: 0.10 g.

where g is the acceleration due to gravity.

Sight distance on sag curves: To Austroads AGRD03 clause 8.6.5.

Side road intersections: Locate intersections of roads at a safe distance from a crest, determined by visibility from the side road. If it is proposed to locate intersections of a side road where a crest occurs, provide details with justifications.

3.10 Auxiliary lanes

3.10.1 General

Requirement: Provide auxiliary lanes adjacent to the through traffic lanes to enhance traffic flow and maintain the required level of service where an Arterial road meets with the Sub-arterial, Collector or Local roads.

3.10.2 Types of auxiliary lanes

Speed change lanes: Provide speed change (acceleration or deceleration) lanes at intersections or interchanges to allow an entering vehicle to access the traffic stream at a speed approaching or equal to 85th percentile speed of the through traffic.

Overtaking lanes/climbing lanes: Provide overtaking lane lengths to Austroads AGRD03 Table 9.2 and merge sight distance at the end of overtaking to Austroads AGRD03 Table 9.3.

Slow vehicle turnouts: Provide a short section of paved shoulder to allow vehicles to pull aside and be overtaken. Provide turnout lengths of 60–160 m for average approach speed of 30–90 km/h and a width of 3.7 m.

3.10.3 Cross-section

Auxiliary lane width: Provide auxiliary lane width not less than the normal width for that section of the road.

Shoulder width: 1 m.

Crossfall: Provide same crossfall of the auxiliary lane as the adjacent lane.

3.11 Intersections

3.11.1 Design criteria

Requirement: Consider the following factors in the location and design of intersections:

- Alignment and grade of approach road.
- Provision of drainage.
- Interference with public utilities.
- Property access.
- Topography.
- Natural and built environment.

Urban and rural intersections: To Austroads AGRD04 Table 4.1.

Road users considerations: To Austroads AGRD04 Table 3.2.

Design criteria: To Austroads AGTM06.

3.11.2 Intersection turning movements

Requirement: Minimise the number of turning movements at intersections or junctions that a driver is required to undertake to reach a particular property within the development.

3.11.3 Intersection types

Traffic management: Select the type of intersections for traffic management in conformance with Austroads AGTM06 Table 2.4.

The basic forms of an intersection may include the following:

- Signalised, unsignalised or a roundabout.
- Channelised (i.e. has traffic islands and/or medians) to develop specific types of intersections, or unchannelised.
- Flared, to provide additional through and/or turning lanes, or unflared.
- Due to different driver expectations for an urban or rural intersection, different design and traffic management guidelines will apply.

3.11.4 Location

- Requirement: Locate intersections to Austroads AGRD04 Table 4.2 and the following:
- Streets intersection: Preferably at right-angles and not less than 70°.
- Landform: Allowing clear sight distance on each of the approach legs of the intersection.
- Minor street: Intersect the convex side of the major street.
- Vertical grade lines at the intersection: Conform to the following:
 - Provide a desirable grade of 3% with a maximum of 5%.
 - Allow for any direct surface drainage.
- For a left turn, where two minor side streets intersect a major street in a staggered pattern, provide a minimum centreline spacing of 40 m.

Traffic volumes: Design for all movements to occur safely without undue delay. Use projected traffic volumes in designing all intersections or junctions on Local sub-arterial roads.

State roads and national highways: Design intersections for the junction of Council's roads with existing state rural or urban roads and national highways to Austroads AGRD04.

Approval of State Road Authority: Design intersections with state roads or national highways in conformance with the requirements of the State Road Authority.

Sight distance: Provide adequate stopping and sight distances for horizontal and vertical curves at all intersections.

Parking: Where required, make appropriate provision for vehicles to park safely.

Drainage: Design the road reserve cross-section profile to satisfy the drainage function of the carriageway and/or road reserve.

Turning movements: Accommodate all vehicle turning movements in conformance with Austroads AP-G34 and the following:

- For intersection turning movements involving Local sub-arterial roads: Provide for the design semi-trailer with turning path radius 19.0 m.
- For intersection turning movements involving Local streets or Collector streets, but not Local sub-arterial roads: Provide for the design single unit bus with turning path radius 12.5 m.
- For intersection turning movements on access streets but not involving local sub-arterial roads, collector streets or local streets: Provide for the garbage collection vehicle used by the local authority.

- For turning movements at the head of cul-de-sac access streets: Provide for sufficient area as per SD 106 for the design single unit truck to make a continuous turn. If driveway entrances are used for turning movements, design the required area to withstand the relevant loads.

Turning radii at intersections or driveways on Local sub-arterial road: Design for the intended movements within desired speeds to be exceeded to Austroads AGRD04 Table 5.1.

Bus facilities: Provide minimum length required for bus lane on an intersection to Austroads AGRD04 Table 6.1.

Minimum width of bicycle and bus lanes: To Austroads AGRD04 Table 6.2.

3.11.5 Sight distance

Requirement: Provide adequate horizontal and vertical sight distance at intersections. Examine each intersection location for conformance with the criteria for Approach Sight Distance (ASD), Minimum gap sight distance (MGSD) and Safe Intersection Sight Distance (SISD). Ensure ASD and SISD are achieved for all intersections, and MGSD where appropriate. Reposition an intersection if required to obtain conformance with the following sight distance criteria:

- ASD: To Austroads AGRD04A Table 3.1 and grade corrections to Austroads AGTM06 Table 3.3 for sealed roads.
- MGSD: To Austroads AGRD04A Table 3.5 for various speeds.
- SISD: Provide SISD for sealed roads to Austroads AGRD04A Table 3.2.

3.11.6 Type of turn treatments

General: Provide the appropriate type of right-turn and left-turn treatments from the following:

- Basic turn treatment (Type BA):
 - Rural basic (BA) turn treatment: To Austroads AGRD04A Figure 4.1.
 - Rural basic left-turn treatment for minor roads: To Austroads AGRD04A Figure 8.2, width minimum length of widened parallel shoulder to Austroads AGRD04A Table 8.1.
 - Urban basic (BA) turn treatment: To Austroads AGRD04A Figure 4.2.
- Auxiliary lane turn treatment (Type AU): Provide short lengths of auxiliary lane to improve safety on high speed roads where an arterial road meets with sub-arterial, collector or local roads. Provide the following turn treatments as appropriate:
 - Rural auxiliary lane turn treatments: To Austroads AGRD04A Figure 4.5.
 - Urban auxiliary lane turn treatments: To Austroads AGRD04A Figure 4.6.
 - Urban auxiliary left-turn treatment – Short turn lane (AUL(S)) major road: To Austroads AGRD04A Figure 8.10 with setting out details of the left turn geometry to Austroads AGRD04A Table 8.4 and with minimum kerb radii for low speed environment to Austroads AGRD04A Table 8.3.
- AUR right turn treatments: Generally, not as safe as a channelised treatment at unsignalised intersections. Do not use, unless approved by State Road Authority.
- Channelised turn treatment (Type CH):
 - Rural channelised (CH) intersection turn treatment: Layout to Austroads AGRD04A Figure 4.7 and design details to Austroads AGRD04A Figure 8.5 and Figure 8.6.
 - Urban channelised (CH) intersection turn treatment: Layout to Austroads AGRD04A Figure 4.8 and design details with a high entry angle left-turn island to Austroads AGRD04A Figure 8.12 and Urban CHL with acceleration lane to Austroads AGRD04A Figure 8.13.

In all cases the minimum intersection shall be a BA right and left treatment

Staggered T-intersections: Rural staggered T intersections may be 'right to left' or 'left to right' type to Austroads AGRD04A Section 4.11. Consider traffic volumes and available width in design selection. Provide staggered T-intersections by:

- Setting out the alignment of the minor roads on new major roads to form a staggered T-intersection.
- Realigning one or both minor road legs of an existing intersection.

3.12 Roundabouts

3.12.1 General

Design criteria: To Austroads AGRD04B Section 4 and Austroads AGTM06 Section 4. If alternative criteria is proposed, submit alternative criteria for consideration.

Requirement: Provide the following:

- Functional design: To achieve safety of all users and traffic performance.
- Entry width: To provide adequate capacity.
- Adequate circulation width: Compatible with the entry widths and design vehicles (e.g. buses, trucks, cars).
- Central islands: To Austroads AGRD04B Table 4.1 with a size sufficient only to give drivers guidance on the manoeuvres expected.
- Deflection of traffic to the left on entry: To promote gyratory movement.
- Adequate deflection of crossing movements to ensure low traffic speeds.
- A simple, clear and conspicuous layout.
- Design so that the speed of all vehicles approaching the intersection will be less than 50 km/h.
- Landscape and street furniture: To Austroads AGRD04B Section 8.3.
- Landscaping of central islands may be considered subject to vegetation maintenance planning considerations, mature height and spread of vegetation and sight distances. In no circumstances shall splitter islands be planted

Approval: Obtain approval of roundabouts from the Council and the relevant State Road Authority.

3.13 Traffic calming

3.13.1 General

Design criteria: Calming devices (e.g. thresholds, slowpoints, speed humps, chicanes and splitter islands) to AS 1742.13 and Austroads AGTM08.

LATM Type: Select the type of local area traffic management devices from Austroads AGTM08 Table 7.1.

Local area traffic management (LATM) devices: Conform to the following:

- Streetscape:
 - Reduce the linearity of the street by segmentation.
 - Avoid continuous long straight lines (e.g. kerb lines).
 - Enhance existing landscape character.
 - Maximise continuity between existing and new landscape areas.
- Location of devices/changes:

- Other than at intersections, maintain consistency with streetscape requirements.
- For compatibility with existing street lighting, drainage pits, driveways, and services.
- Slowing devices optimally at spacings of 100 m to 150 m.
- Design vehicles:
 - Make sure emergency vehicles are able to reach all residences and properties.
 - Local streets with a feeding function between arterial roads and minor local streets may be designed to Austroads AP-G34 turning templates.
 - Bus routes: Allow buses to pass without mounting kerbs and with minimal discomfort to passengers.
 - Provide for building construction traffic in newly developing areas where street systems are being developed in line with LATM principles.
- Control of vehicle speeds:
 - Reduce speed using devices which shift vehicle paths laterally (slow points, roundabouts, corners) or vertically (humps, platform intersections, platform pedestrian/school/bicycle crossings).
- Create a visual environment conducive to lower speeds. This can be achieved by segmenting streets into relatively short lengths (less than 300 m), using appropriate devices, streetscapes, or street alignment to create short sight lines.
- Visibility requirements (sight distance):
 - Provide critical sight distances so that evasive action may be taken by either party in a potential conflict situation. Relate sight distances to likely operating speeds.
 - Consider sight distance to include those of and for drivers, pedestrians and cyclists.
 - Design for night time visibility of street features. Locate speed control devices near existing street lighting if practicable and delineate all street features/furniture for night time operation. Provide additional street lighting at proposed new speed control devices located away from existing street lighting.
- Safety: Provide roadside design that conforms with Austroads AGRD06 including:
 - Safety barriers.
 - Treatment options.
 - Steep down grades.

3.13.2 Critical dimensions.

Dimensions: Conform to the following:

- Pavement narrowing:
 - Single lane between kerbs: 3.50 m.
 - Single lane between obstructions: 3.75 m.
 - Two lane between kerbs: Minimum 5.50 m.

Plateau or platform areas: 75 mm to 150 mm height maximum, with 1 in 15 ramp slope relative to road grade.

Width of clear sight path through slowing devices: 1.0 m maximum (i.e. the width of the portion of carriageway which does not have its line of sight through the device blocked by streetscape materials, usually vegetation).

Mountable areas required for the passage of large vehicles: To appropriate turning templates.

Approval: Obtain approval of traffic calming devices from the Council.

3.13.3 Bus routes

Criteria: Conform to the following:

Design the road hierarchy to cater for buses on routes identified by the Council.

Location of bus routes and bus stops: Arrange so that no more than 5% of residents have to walk in excess of 400 metres to catch a bus.

Design roads above the Local street level in the network hierarchy as bus routes.

3.13.4 Bus route criteria

Refer to Council's Standard Drawings

3.14 Parking

Applicants are directed to the following technical documents which must be read in conjunction with this Section of the DCP:

- Australian Standards – Parking Facilities – AS2890 series as applicable:
- Austroads & any relevant Roads & Maritime Services supplements –
- TDT 2001/06a – Autoturn Swept Path Computer Program.
- Roads & Maritime Services Traffic Generation Rates Austroads – Design Vehicles and Turning Templates

3.14.1 On-site parking

Requirement: Determine the demand for on-site parking to Council DCP Requirements.

Design criteria:

- Accommodate on-site parking requirements for normal levels of activity associated with any land use.
- Do not impede through traffic.
- Dimensions: Allow convenient and safe access and usage.
- Non-residential land uses:
 - Number of parking spaces: To parking standards as determined by the relevant authority.
 - Layout and access: To AS/NZS 2890.1.
 - Parking for people with disabilities: To AS/NZS 2890.6 and to the AUS Gov Act No. 135 - *Disability Discrimination Act 1992*.
- Residential land use: Number of parking spaces: Conform to the following:
 - Single dwelling allotment: Provide two car parking spaces.
 - Multi-unit residential developments: Provide three spaces on-site for each two dwelling units.
- Minimum dimension: Include one space for each residential unit within the allowable building area and with a minimum dimension of 5.0 m by 3.0 m.

3.14.2 On-street parking

Standards: To AS 2890.5, Austroads AGRD03 clause 4.10 and Austroads AGTM11.

Road reserve parking: Provide adequate parking within the road reserve for visitors, service vehicles and any excess resident parking.

Future spaces: On single lane carriageways, provide one space for each two allotments on the verge within 25 m of each allotment, with scope to provide one additional space for single dwelling allotments or for each two units in a multi-unit development if required at a future time.

Short term truck parking: On single lane carriageways, combine a number of verge spaces to provide for short term truck parking within 40 m of any allotment.

Verge and carriageway parking: On single lane access streets, provide parking spaces within the verge. Provide verge and carriageway parking in conformance with the following:

- Adequate dimensions.
- Convenient and safe to access.
- Well defined with traffic control devices.
- All-weather surface.
- No restriction to the safe passage of vehicular, disabled and pedestrian traffic.

Joint use: For non-residential land uses, provide the opportunity for maximum joint use of shared parking by a number of complementary uses.

On-street parking dimensions: Conform to the following:

- Single (car) space: 6.5 m x 2.5 m.
- Combined spaces for two cars: 13.0 m x 2.5 m.
- Truck parking: 20 m x 2.8 m with adequate tapers at both ends to allow parking manoeuvres determined to Austroads AP-G34.

Material: Construct all verge spaces and indented parking areas of concrete, interlocking pavers, lawn pavers, bitumen with crushed rock or other suitable base material designed to withstand the loads and manoeuvring stresses of vehicles expected to use those spaces.

Angled parking: Provide angled parking only on Access streets and Local streets where speeds do not exceed 40 km/h.

Angled parking space widths: To AS 2890.5 Table 2.2.

3.14.3 Off-street parking

Standards: To AS/NZS 2890.1, Austroads AGTM11 and Austroads AGRD06B.

4 Documentation

4.1 General

4.1.1 Design process

Design development process: Develop a flow chart to capture the design process, include processes such as the brief and scope development, investigative studies and analyses, consultation, selection of design parameters/design inputs, design reviews, major design decisions made or design outputs, approvals and critical dates.

Design review, verification and validation: Provide design documentation to Austroads AGRD08.

4.1.2 Related design documentation requirements

Drainage and run-off: To the *D09 Stormwater drainage (Design)* and *D07 Subsurface drainage (Design)* worksections.

Earthworks, contours, cut and fill: To the *D04 Site regrading* worksection.

Footpaths, pathways and cycleways: To the *D10 Pathways and cycleways (Design)* worksection.

Pavement structure: To *D06 Pavement design* worksection.

4.1.3 Approvals

Requirement: Document any prerequisite for approval of the development advised by the following authorities:

- Council for:
 - Construction staging and traffic management.
 - Landscaping and verge design.
 - Access provisions.
 - Tree protection and vegetation clearing.
 - Stormwater drainage control.
- Planning and water resources department: For general land use, salination prevention measures, existing water bodies that may be affected, and areas of heritage significance.
- The EPA: For other general environmental impact requirements.
- Utilities authority: For any public or private utility affected by the development.
- Rail transport authority: For crossings and rail conflicts.

Authority audits: Include first party, external or third party audits, for design process or design products, required by the relevant authority.

4.2 Drawings

4.2.1 Drawing sheets

Requirement: Provide separate sheets for the following:

- Cover.
- Key/locality plan and legend.
- Plans.
- Longitudinal sections.
- Cross-sections.
- Structural details.
- Standard drawings.

Minimum requirements: Complete the relevant checklist in Annexure B of the *D02 Quality requirements for design* worksection for the development. Make sure required items are included in the design documentation.

4.2.2 Drawing presentation

Plain English: Drawings form part of the permanent record and are legal documents. Keep terminology in plain English, so that drawings can be easily read and understood by those involved in the construction of the Works.

Drawings size and format: Present drawings on A1 sheets unless otherwise authorised. Prepare clear and legible drawings with consistent lettering and style, and clearly referenced with notations and tables as appropriate.

Drawing scales: Conform to the following:

- Plans:
 - Generally: Minimum 1:500.
 - Rural plans: Minimum 1:1000.
- Longitudinal sections:
 - Horizontal: Minimum 1:500.
 - Vertical: Minimum 1:100.
- Cross-sections: 1:100.

Requirement: Provide the following drawings, describing the geometric road layout for the development:

- Survey(s): Showing contours, original and proposed terrain, locations of existing and new roads. If required, include finished grades on a digital terrain model.
- Plans: Showing alignments of existing and new roads, access treatments, drainage structures, edges of pavement, roadside barriers and flares, clearing and grubbing limits, critical dimensions, cut/fill toes, utility conflicts, objects/items that are to be relocated or removed, fencing, and limits of construction.
- Ground profiles: Showing proposed grades, vertical curve data, horizontal alignment schematic, superelevation, existing and proposed culvert locations, surcharge and preload areas, and original ground profile.
- Typical sections drawings: Showing lane and shoulder widths, clear zone requirements, excavation and embankment slopes, stripping, and special treatments.
- Laning and geometrics (vertical and horizontal): Showing access movements, intersection movements, design vehicles (and turning templates), design speed, approaches and transitions, vertical clearances, and critical laning dimensions.
- Signing and pavement marking drawings: Showing new sign locations, schedule of signs required, sign removals and relocations.
- Construction staging drawings: Showing detours if required, any required cross-sections.
- Utility relocation drawings.
- Landscaping drawings: Showing verge treatments.
- Environmental drawings: Showing sensitive zones, limits and setbacks from environmental features.
- Supporting design documents.

Supporting design documents

4.2.3 Design reports

Requirement: Provide a report including the following:

- Geotechnical field data.
- Noise studies.
- Environmental and archaeological studies.
- Development connectivity: Include details of links and place functions.
- Strategies for achieving target operating speeds.

Environmental impact statement: Include details of potential impacts and measures adopted for minimising the impact.

4.2.4 Design calculations

Calculations: Provide results and details of software used for relevant distance or curvature calculations. If friction is a factor in layout/geometry, note the pavement type assumed for surface conditions and noise minimisation.

Assumptions: Include any data used in the design calculation.

4.2.5 Specifications

Requirement: Refer to Council's Engineering Construction Specifications.

4.2.6 Design certification

Certificate: Provide a signed and dated design certificate as evidence that a Professional Engineer has reviewed all the design documents, including program and plans for the development, and can verify that the geometric road layout requirements for the development meet the Council and statutory requirements. Refer D02-Annexure A-Sect 3.1.1

4.3 Work-as-executed

4.3.1 Work-as-executed documents

Work-as-executed drawings: Provide an additional set of final construction drawings for the purpose of recording the work completed by the Contractor.

Data standard for road management: To Austroads AP-R597.

Provide all required data and electronic files as outlined in WSC “Work as Executed plans specification and attribute requirements” located on councils website.

4.3.2 Final certification of completed works

Requirement: Council requires the Designer or its representative to carry out sufficient site inspections to validate the final certification of the proposed works.

Completed works: The Designer to provide evidence of the inspections undertaken during construction works and a copy of the final certification that the completed works is consistent with the approved design.

5 Annexure

5.1 Annexure - Referenced documents

The following documents are incorporated into this worksection by reference:

AS 1742		Manual of uniform traffic control devices
AS 1742.13	2009	Local area traffic management
AS 2890		Parking facilities
AS/NZS 2890.1	2004	Off-street car parking
AS/NZS 2890.2	2018	Off-street commercial vehicle facilities
AS 2890.5	1993	On-street car parking
AS/NZS 2890.6	2009	Off-street parking for people with disabilities
AS/NZS 3845		Road safety barrier systems and devices
AS/NZS 3845.1	2015	Road safety barrier systems
AS 5488		Classification of Subsurface Utility Information (SUI)
AS 5488.1	2019	Subsurface utility information
AS 5488.2	2019	Subsurface utility engineering
Austrroads AG RTP	2009	Guide to road transport planning
Austrroads AGRD		Guide to road design
Austrroads AGRD01	2015	Introduction to road design
Austrroads AGRD02	2019	Design Considerations
Austrroads AGRD03	2016	Geometric design
Austrroads AGRD04	2017	Intersections and crossings - General
Austrroads AGRD04A	2017	Unsignalised and signalised intersections
Austrroads AGRD04B	2015	Roundabouts
Austrroads AGRD06A	2017	Paths for walking and cycling
Austrroads AGRD06	2010	Roadside design, safety and barriers
Austrroads AGRD06B	2015	Roadside environment
Austrroads AGRD07	2008	Geotechnical investigation and design
Austrroads AGRD08	2009	Process and documentation
Austrroads AGTM		Guide to traffic management
Austrroads AGTM03	2017	Traffic studies and analysis
Austrroads AGTM04	2016	Network management
Austrroads AGTM05	2019	Road management
Austrroads AGTM06	2019	Intersections, interchanges and crossings
Austrroads AGTM07	2019	Traffic management in activity centres
Austrroads AGTM08	2016	Local area traffic management
Austrroads AGTM11	2017	Parking
Austrroads AGTM12	2019	Traffic impacts of developments
Austrroads AP-C87	2015	Austrroads glossary of terms. 2015 edition.
Austrroads AP-G34	2006	Austrroads design vehicles and turning path templates (Includes CD)
Austrroads AP-R597	2019	Data Standard for Road Management and Investment in Australia and New Zealand Version 3.0
AUS Gov Act No. 135	1992	Disability Discrimination Act
SOCC Guide	2018	Guide to codes and practices for streets opening
Council Street Tree Master Plan		